Motorized shears

Typ: TS, TS-M

Machines of type TS, and models TS-M 06/12, TS-M 10/10 are shears of steel construction suitable for cutting thin sheet metal, printed circuit boards, plastics and etc.

They are normally equipped with the simple manual back gauge with the possibility of cutting at an angle and with an illuminated shearing line.

Back gauge is equipped with a millimeter scale. They are equipped with LED lighting cutting line, the front and rear angle gauge, and are driven by an electric motor and are suitable for use in series production.

We can supply on request of customer the stand that facilitates operation of the machine.

The machine is easy to maintain and operate. The manual version is marked as type TS.

Standard equipment:

- LED cutting line light
- automatic sheet holder
- back gauge with milimeter scale
- front angle stop
- control pedal
- back safety system (only TS-M)

Special equipment:

- special knives
- stand
- shadow line lighting (substitude LED cutting line light)

We recommend:

Folding machines TB

Technical parameters of motorized shears TS-M

Model	Shearing length	Max. sheet thickness steel 400N/mm²	Max. sheet thickness stainless 600N/mm²	Max. sheet thickness aluminium 275N/mm²	Cuts number / min.	Motor	Table width	Table height	Length	Width	Height	Weight
	mm	mm	mm	mm	-	kW	mm	mm	mm	mm	mm	kg
06/12	650	1,25	0,90	1,70	54	0,75	265	270	885	940	500	110
10/10	1000	1,00	0,70	1,30	54	0,75	265	340	1250	950	535	185

H.M.Transtech spol. s.r.o
Volgogradská 13/B, 080 01 Prešov, Slovakia
e-mail: sales@hmtranstech.com, www.hmtranstech.com
tel.: +421 51 7718 516

Producer reserves the right to change all specifications subject without notice.
For current information about our products visit www.hmtranstech.com